

Class Rule Changes

International 420 Class Association

Effective date: 2025-03(March)-01

Status: Approved



Amendment One

F.2.4.19

Old:

F.2.4.19 A device for preventing the mainsail from being set above the **upper point**, to ensure compliance with C.10.3.2.2, unless the mainsail halyard is set on a lock or tooth rack as in F.2.4.3.

Amend to read:

F.2.4(u) A device for preventing the mainsail from being set above the **upper point**, ~~to ensure compliance with C.10.3(b)2~~, unless the mainsail halyard is set on a lock or tooth rack as in F.2.4(c) ~~Adjustable Sail track stops with screws or fixed stiff materials inside the mast track are acceptable devices. Rivets in the sail track are not suitable devices~~

Amendment Two

F.3.4.1.5

Old:

F.3.4.1.5 A device for preventing the mainsail from being set outside the **outer point**, to ensure compliance with C.10.3.2.2.

Amend to read:

F.3.4(a)5 A device for preventing the mainsail from being set outside the **outer point**, to ensure compliance with ~~C.10.3(b)2. Adjustable Sail track stops with screws or fixed stiff materials inside the boom track are acceptable devices. Rivets in the sail track are not suitable devices.~~

Amendment Three

E.3.4.(b)

Old:

E.3.4.(b) One **centreboard** downhaul of rope and elastic, one fairlead and/or one block and one cleat without moving parts on the centreboard case capping. A wedge is permitted under the cleat.

Amend to read:

E.3.4.(b) One **centreboard** downhaul of rope and elastic, one fairlead and/or one block ~~and~~. One cleat without moving parts on the centreboard case capping. A wedge is permitted under the cleat.

Class Rule Changes

International 420 Class Association

Effective date: 2025-03(March)-01

Status: Approved



Amendment Four

E.3.5

Old:

- E.3.5 The direction of the control ropes used for the adjustment of the **centreboard** shall be modified only by means of the blocks and fairlead and block specified in rule E.3.4.

Amend to read:

- E.3.5 The direction of the control **lines** used for the adjustment of the **centreboard** shall be modified only by means of the blocks **specified in E.3.4(a) and fairlead and block specified in rule E.3.4(b).**